

## FEATURES AND BENEFITS

- Manufactured from EPDM or silicone rubber, Roofjack™ RD is compounded for maximum resistance to ozone, UV light, & temperature extremes.
- Flexible aluminum base will allow the flashing to conform to any metal roof configuration. Pipe location can be centered in the flat of the panel or the rib. Urethane sealant & self-drilling screws complete the installation
- Roofjack RD are well marked so they can easily be cut with shears to fit exactly the pipe size used.
- Roofjack RD are available in Black or Gray EPDM as well as Red or Gray high temperature Silicone.

# RoofjackRD™



|    | PIPE SIZE     | BASE DIAMETER       | COLOR MATERIAL                             | CARTON QUANTITY | WEIGHT PER CARTON |
|----|---------------|---------------------|--|-----------------|-------------------|
| #1 | 1/4" -2-1/2"  | 4.75"<br>(120.7mm)  | Black/Gray<br>EPDM & Red/<br>Gray Silicone | 15              | 2.5               |
| #2 | 1-3/4"-3"     | 6.21"<br>(157.7mm)  | Black/Gray<br>EPDM & Red/<br>Gray Silicone | 15              | 4.5               |
| #3 | 1/4"-5"       | 7.74"<br>(196.6mm)  | Black/Gray<br>EPDM & Red/<br>Gray Silicone | 15              | 7.5               |
| #4 | 3"-6-1/4"     | 9.26"<br>(235.2mm)  | Black/Gray<br>EPDM & Red/<br>Gray Silicone | 10              | 8.0               |
| #5 | 4-1/4"-7-3/4" | 10.75"<br>(273.0mm) | Black/Gray<br>EPDM & Red/<br>Gray Silicone | 10              | 9.5               |
| #6 | 5" - 9"       | 12.50"<br>(317.5mm) | Black/Gray<br>EPDM & Red/<br>Gray Silicone | 10              | 12.0              |
| #7 | 6" - 11"      | 14.60"<br>(370.8mm) | Black/Gray<br>EPDM & Red/<br>Gray Silicone | 10              | 15.5              |
| #8 | 7" - 13"      | 16.5"<br>(419.1mm)  | Black/Gray<br>EPDM & Red/<br>Gray Silicone | 5               | 12.8              |
| #9 | 9" - 19"      | 25.25"<br>(641.1mm) | Black/Gray<br>EPDM & Red/<br>Gray Silicone | 5               | 19.3              |

**HIGH TEMPERATURE SILICONE IS NOW AVAILABLE IN GRAY**

## EASY INSTALLATION



1. Choose pipe opening and trim

2. Slide over pipe



3. Form to roof profile

4. Apply sealant

5. Fasten to complete

|   | EPDM 500                           | SILICONE                           |
|---|------------------------------------|------------------------------------|
| Advanced Ozone Resistance Tested to...                              | 70 hr @500 pphm                    | 70 hr @ 500 pphm                   |
| High Temperature Resistance Tested to<br>Intermittent<br>Continuous | +135°C (+275°F)<br>+100°C (+212°F) | +260°C (+500°F)<br>+225°C (+500°F) |
| Low Temperature Resistance tested to...                             | -55°C (-65°F)                      | -74°C (-100°F)                     |
| Tensile Set Maximum...  | 10MPa (1450psi)                    | 5MPa (700psi)                      |
| Compression Set Maximum...  | 25%                                | 50%                                |

